

Cut n Break Quick Start guide

Here's a more detailed breakdown:

1. Preparation:

- **Safety First:** Always wear appropriate personal protective equipment (PPE), including a helmet, hearing protection, goggles or visor, breathing mask, gloves, and sturdy boots with steel toe caps.
-
- **Check Fuel and Oil:** Ensure the saw has sufficient fuel and oil.
-
- **Check Safety Features:** Inspect the cutting blade for damage, ensure the guard is in good condition, and the throttle control and lockout move freely.
-
- **Decompression Valve:** Press the decompression valve before starting.
-
- **Choke:** If the engine is cold, pull the choke control out.
-

2. Starting:

- **Throttle Lockout:** Engage the throttle lockout.
-
- **Start the Engine:** Pull the starter handle firmly until the engine starts.
-
- **Warm-up:** Let the engine run for a minute to warm up.
-
- **Choke (if needed):** If the engine is still cold, you may need to adjust the choke.
-
- **Full Throttle:** Once warmed up, apply full throttle.
-

3. Cutting:

- **Depth Stop:** Adjust the depth stop to the desired cutting depth.
- **Water Supply:** Turn on the water supply if using wet cutting.
- **Engage Throttle:** Squeeze the throttle lever to engage the blade.
- **Cut:** Gently lower the blade into the material and move the saw forward at a steady pace.
- **Don't Force:** Allow the blade to cut freely without excessive force.
- **End of Cut:** At the end of the cut, lift the blade out of the material, release the throttle, and let the blade stop before moving.
-

4. Breaking:

- **Breaking Tool:** Use the accompanying breaking tool to remove the core from the cut.
-

5. Safety Reminders:

- **Avoid Heights:** If possible, avoid working at heights.
- **Manual Handling:** Be aware of manual handling risks.
- **Vibration and Dust:** Minimize exposure to vibration and dust.
- **Kickbacks:** Be aware of the risk of kickbacks.
- **Combustible Materials:** Be cautious of sparks igniting combustible materials.